Spirit Universal Innovated to be used with

any suitable faucet

Yes

Yes

Yes

Yes

No

No

Yes

Flow [litres/day] 2521

Flow [USGAL/day] 666

Recovery [%] 53.2

Features

11

Technical Properties

BLUEWATER

Product Identifiers	
Product name	Spirit Universal
Product code	Spirit 300 Cp
Purification Technology	
SuperiorOsmosis™	
China	
Product number	919240241
Voltage	230V~ 50/60 Hz
Power consumption [W]	350
Plug / Type	Grounded Chinese /
Europe	
Product number	919240261
Voltage	230V~ 50/60 Hz
Power consumption [W]	350 Croupdad European / C
Plug / Type	Grounded European / F
UK Dua duat avaala av	010240201
Product number	919240281 230V~ 50/60 Hz
Voltage Power consumption [W]	230V~ 50/60 H2 350
Plug / Type	Grounded UK / G
US	
Product number	919240252
Voltage	120V~ 60 Hz
Power [Amps]	3
Plug / Type	Grounded American / B
Dimension W x D x H	
Product dimension [mm]	150 x 365 x 462
Product dimension [inch]	5.9 x 14.4 x 18.2
nstallation dimension [mm]	190 x 482 x 460
nstallation dimension [inch]	7.5 x 19 x 18.1
Weight	
18.1 kg / 39.9 lbs packaged w	eight
Prefiltration	
Granulated Activated Carbon	(GAC) prefilter
Activation Type	
Pressure Controlled (On / Off	f, 3 / 4 [bar])
Faucet	
Faucet included on some ma Customized faucet must be s	
Features	
low prossure protection stop	No

Run time meter
Water quality indicator
Water quality alarm
Water quality stop
Suitable for brackish water
Clean water rinse valve
Compatible with household appliances

Requirements of Inlet Water

Pressure [psi]	22-145
Flow [l/min]	>6
TDS [mg/l]	<1200
Conductivity [µS/cm, 25 °C]	<1600
Temperature	2-35 [°C] / 35.6-95 [°F]
Hardness [mg/l]	<100
Iron Fe(II) [mg/l]	<0.3
Iron Fe(III) [mg/l]	<0.5
Turbidity [FNU]	<0.5

Maintenance

Granulated Activated Carbon prefilter	4-6
High Rejection Membrane	months
Reduction Performance	4-6 years
58 for below listed substances	Jere Jere J
Salt Rejection [TDS]	95.3%

Salt Rejection [TDS]	95.33



Low pressure protection stop	No
Low pressure protection automatic restart	No